


Hoisting Unit		
Electric hoist	type	MHL6-25 4/1 H18 V4
Capacity	t	10,0
Mode of operation	---	2m
Lifting height	m	18
Dia Rope	mm	Φ15
Lifting speed	m/min	4
Output	kW	8,0
Speed of revolution	min ⁻¹	920
Current	A	24,5
Travelling Mechanism		
Travelling speed	m/min	20
Geared motor	type	2xKAT80A-6-35
Output	kW	2x0,37
Speed of revolution	min ⁻¹	905
Current	A	1,45
Travel wheel diameter	mm	160
Travel wheel max. pressure	t	1,4
Power supply	---	3 ph / 400V / 50Hz
Control	---	pendant
Operation	---	indoor

					Озн. на грапавост БДС-ISO 1302: Ra	Озн. на формата и разп. БДС-ISO 1101-1	Неозн. допуски БДС-ISO 2768
					БДС-ISO 128	Маса (kg) 1023.42	Материал:
Изм.	Брой	Номер	Подпис	Дата	Лист 1/1	 balkancarpodem	Кат. №: Чертеж №: EKN20 MHL6-25 4/1 H18 V4
Разр.	Татарлиев		5.5.2021				
Пров.			5.5.2021				
Утв.	Кавалов		5.5.2021		Мащаб 1:10		
Наименование: Monorail trolley, standard headroom							